

### STEALTH BREAKER SPECIFICATIONS

ITEM	UNITS	MB20EXS	MB30EXS	MB40EXS	MB50EXS	MB60EXS	MB70EXS	MB80EXS	MB100EXS
Impact Energy Class	ft-lb	1500	2000	3000	5000	6000	7500	8500	12000
	J	2034	2712	4068	6780	8136	10170	11526	16272
Oil Flow Range	gpm	15 - 25	20 - 30	24 - 35	32 - 45	37 - 50	45 - 63	51 - 67	55 - 80
	lpm	56 - 95	76 - 114	90 - 130	120 - 170	140 - 190	170 - 240	190 - 250	208 - 302
Maximum Hydraulic Pressure	psi	2500	2500	2500	2700	2700	2700	2700	2700
	bar	172	172	172	186	186	186	186	186
Blows Per Minute Range	blows per minute	360 - 800	500 - 700	400 - 600	400 - 500	300 - 450	300 - 400	280 - 370	230 - 320
Weight (with tool bit)	lb	1259	1898	2859	3964	4566	5803	6246	8799
	kg	571	861	1297	1798	2071	2632	2833	3991
Length (with tool bit)	in	71	77	89	96	105	110	117	128
	mm	1802	1962	2264	2451	2656	2783	2962	3241
Tool Working Length	in	18.3	19	25	29	31.5	33.6	35.2	35
	mm	466	486	646	727	800	853	895	890
Tool Diameter	in	3.3	3.9	5	5.5	5.9	6.1	6.5	6.9
	mm	84	100	127	140	150	155	165	175
System Relief	psi	3000	3000	3000	3100	3100	3100	3100	3100
	bar	207	207	207	214	214	214	214	214
Noise Level 85 dBA @ distance	ft	20 - 40	23 - 46	33 - 59	52 - 72	69 - 98	85 - 115	115 - 130	125 - 148
	m	6 - 12	7 - 14	10 - 18	16 - 22	21 - 30	26 - 35	35 - 40	38 - 45

**NOTE:** Weights, dimensions and operating specifications listed on this sheet are subject to change without notice. Where specifications are critical to your application, consult your dealer or Stanley Hydraulic Tools.



**MB60EXS  
Breaker**

Mounting bracket not included, must be ordered separately.

### STEALTH BREAKER FEATURES

- S Silenced.** Noise suppression features make the new Stanley breakers some of the quietest on the market today.
- T Trimmed.** Narrower profile allows the breaker to work closer to the walls of a trench and give better visibility for the operator.
- E Enclosed Housing.** The powercell is suspended between bumpers eliminating damaging shocks transmitted to the carrier.
- A Armored Lower End.** The housing is double strength at the lower end of the breaker to fully protect the powercell.
- L Lighter Weight.** New generation stealth breakers are lighter in weight, allowing use of a lighter, less expensive carrier.
- T Two Moving Parts.** Translates into less maintenance, better performance, and significantly less service.
- H Hard Hitting.** Stanley breakers, pound for pound, are the hardest hitting breakers in their class.

## ORDERING INFORMATION


Model	Description
MB20EXS	STEALTH Mounted Breaker, with 33063 Cross-Cut Chisel Bit
MB30EXS	STEALTH Mounted Breaker, with 32982 Cross-Cut Chisel Bit
MB40EXS	STEALTH Mounted Breaker, with 32987 Cross-Cut Chisel Bit
MB50EXS	STEALTH Mounted Breaker, with 32992 Cross-Cut Chisel Bit
MB60EXS	STEALTH Mounted Breaker, with 43516 Cross-Cut Chisel Bit
MB70EXS	STEALTH Mounted Breaker, with 32997 Cross-Cut Chisel Bit
MB80EXS	STEALTH Mounted Breaker, with 43676 Cross-Cut Chisel Bit
MB100EXS	STEALTH Mounted Breaker, with 33002 Cross-Cut Chisel Bit

## TOOL BITS

Model	Blunt	Cross-Cut Chisel	Line-Cut Chisel	Universal (Conical)	Moil Point
MB20EXS	33057	33063	33065	33061	N/A
MB30EXS	32979	32982	32983	32981	32980
MB40EXS	32984	32987	32988	32986	32985
MB50EXS	32989	32992	32993	32991	32990
MB60EXS	43515	43516	43517	43518	N/A
MB70EXS	32994	32997	32998	32996	32995
MB80EXS	43675	43676	43677	43678	N/A
MB100EXS	32999	33002	33003	33001	33000

## OPTIONAL EQUIPMENT

### AutoLube Kit



The Stanley **AutoLube Kit** provides automatic tool bit/bushing lubrication on STEALTH series breakers.

Proper use of the **AutoLube Kit** prevents premature bushing failure due to lack of lubrication.

The self-contained **AutoLube Kit** is mounted directly on the breaker, making it ideal for use on rented breakers. A low-level indicator on the **AutoLube** pump signals when the grease level is low. The flexible design reservoir can be refilled by changing a standard 14.5 oz. cartridge or by bulk fill.

Model	AutoLube Kit
MB20EXS / MB30EXS	44882
MB40EXS	45112
MB50EXS / MB60EXS	45113
MB70EXS / MB80EXS / MB100EXS	45114

### Mounting Bracket



Stanley mounting brackets are custom-designed to fit your carrier and attach to the carrier by using the existing bucket pins. The capscrews and nuts necessary to attach the bracket to the breaker housing are included with the breaker.

## WARRANTY

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

## CARRIER SIZE

Model	Excavator
MB20EXS	10,000 - 25,000 lb 4,550 - 11,350 kg
MB30EXS	18,000 - 35,000 lb 8,200 - 15,900 kg
MB40EXS	30,000 - 50,000 lb 13,650 - 22,700 kg
MB50EXS	41,000 - 65,000 lb 18,600 - 29,500 kg
MB60EXS	46,000 - 68,000 lb 20,900 - 30,850 kg
MB70EXS	58,000 - 85,000 lb 26,350 - 38,600 kg
MB80EXS	60,000 - 100,000 lb 27,250 - 45,400 kg
MB100EXS	80,000 - 130,000 lb 36,300 - 59,000 kg

Model	Backhoe
MB20EXS	10,000 - 25,000 lb 4,550 - 11,350 kg
MB30EXS	20,000 - 28,000 lb 9,100 - 12,700 kg

MEMBER



The Mounted Breaker  
Manufacturers Bureau of  
the Construction Industry  
Manufacturers Association

**STANLEY**

Stanley Hydraulic Tools

3810 SE Naef Road  
Milwaukie, OR 97267 USA

Tel 503-659-5660  
Fax 503-652-1780

www.stanleyworks.com  
1-800-549-0517